



WULING GOLF CART



| Brand | | Wuling | |
|--|---------------------------------------|---|-----------------|
| Model Description | | Wuling Golf Cart 2 Seater | |
| Model | | WLDT2 | |
| Voltage | | 48v (8v*6) | |
| Dimension Parameters | Dimension(mm) | Length | 2306 |
| | | Width | 1200 |
| | | Height | 1706 |
| | Wheelbase (mm) | | 1660 |
| | Track width | Front (mm) | 875 |
| | | Rear(mm) | 980 |
| Mass parameters | Curb weight (kg) | | 435 |
| | Maximum total mass (kg) | | 670 |
| | Min. axle load mass (kg) | Front axle | 153 |
| | | Rear axle | 282 |
| | Passenger capacity | | 2 |
| Through parameter | Min. turning diameter (m) | | 5.3 |
| | Min.ground clearance (full load) (mm) | | 91 |
| | Angle of approach (full load) (°) | | 72.3 |
| | Departure Angle (full load) (°) | | 35.1 |
| | Front suspension (mm) | | 238 |
| | Rear suspension (mm) | | 408 |
| | Max. speed (full load) (km/h) | | 24 |
| performance | Max. climb % (°) | | 30(17.2) |
| | Cruising range(km) | | 90 - 110 |
| | Suspension frame | | |
| Suspension frame | Front suspension | Horizontal leaf spring independent suspension | |
| | Rear suspension | Integral bridge type non-independent suspension | |
| Tires | Type of tire | Pneumatic rubber tire | |
| | Tire specification | 18x8.5-8 | |
| Electric Motor | Brand | HEPU POWER | |
| | Model | HPQ3 - 60C | |
| | Rated Current (A) | 80 | |
| | Rated Voltage (V) | 48 | |
| Off-vehicle Charger | Charging Time(H) | 08-Jun | |
| | Input Voltage | 85-265VAV | |
| | Maximum Output Voltage(V) | 67.2 | |
| | Maximum Output Current (A) | 20 | |
| Motor Controller | Brand | CURTIS | |
| | Model | 1232SE | |
| Battery | Brand | Trojan / Leoch | |
| | Model | T - 875 / DT876 | |
| | Voltage | 8 | |
| | Capacity of Battery | 170 | |
| Rear axle | Brand | Liuzhou Wuling | |
| | Rear axle full load | 460 | |
| Suspension | | | |
| Front swing arm assembly | | S | |
| Front shock absorber | | S | |
| Front leaf spring assembly | | S | |
| Front left and right knuckle with hub assembly | | S | |
| Rear axle assembly | | S | |
| Rear axle leaf spring and bushing assembly | | S | |
| Rear shock absorber assembly | | S | |

| Braking | |
|--|---|
| Mechanical rear drum brake | S |
| Hydraulic front disc rear drum brake | - |
| Parking brake | S |
| Electronic brake | - |
| Pedal unit | S |
| Interior and Exterior Features | |
| Ball clamping position | O |
| Tee position (racking tool) Tee | O |
| Water cup position | S |
| Left front combination lamp assembly | S |
| Right front combination lamp assembly | S |
| Rear combination lamp assembly | S |
| Ashtray | O |
| Sand pot fixed bandage | O |
| GPS interface and installation position | O |
| Instrument panel storage box | S |
| Solar roof | O |
| Ice bucket fixing mechanism | O |
| Rain cover | O |
| Standing mechanism and guardrail of tail caddie | O |
| Installation hole of sand rake seat | S |
| Remarks: "s" standard configuration, "O" optional configuration, "-" not assembled | |









